

<b>EXN-SERIES Specifications</b>		<b>EXN10</b>
<b>Output power @ 1kHz</b>	<b>8 ohms</b>	1450W x 2
	<b>4 ohms</b>	2900W x 2
	<b>2 ohms</b>	5000W x 2
	<b>8 ohms : Bridge</b>	5800W
	<b>4 ohms : Bridge</b>	10000W
<b>Frequency response</b>		20Hz - 25kHz; +0dB, -3dB
<b>Damping factor</b>		> 500 @ 20Hz - 200Hz
<b>Input sensitivity</b>		0.7V
<b>Input Impedance</b>		20kΩ balanced and 10kΩ unbalanced.
<b>Limiter mode</b>		Soft
<b>Output circuitry</b>		Class HD+ Technology
<b>Cooling</b>		Heat Sink Modules & Automatic Fan Control
<b>Protection</b>		VI limiter, Direct Current Protection (DC), Short Circuit Protection, Current Limiter, Voltage Clip Limiter
<b>Connector Input</b>		XLR-F,XLR-M
<b>Connector Output</b>		NL4 SPEAKON 4 pole and Binding post per CH.
<b>Front panel indicator</b>		Power ON, Signal, Clip Indicator
<b>Dimension W x D x H mm</b>		483 x 590 x 100 mm
<b>Power Supply</b>		Dual EE Core Transformer
<b>Operating voltage</b>		180 ~ 240V, 50 ~ 60Hz
<b>Net weight</b>		19kg

Digitclass Co.,Ltd.  
7/102 Moo 2, Bangpood, Pak-Kret  
Nonthaburi. 11120 Thailand.  
Tel. +668 6447 4041, +66 2583-5928  
Line: @digitclass  
Facebook:Digitclass