

EXN-SERIES Specifications		EXN15
Output power @ 1kHz	8 ohms	2000W x 2
	4 ohms	3800W x 2
	2 ohms	6000W x 2
	8 ohms : Bridge	7600W
	4 ohms : Bridge	12000W
Frequency response		20Hz - 25kHz; +0dB, -3dB
Damping factor		> 500 @ 20Hz - 200Hz
Input sensitivity		0.7V
Input Impedance		20kΩ balanced and 10kΩ unbalanced.
Voltage gain		44dB
Limiter mode		Soft
Output circuitry		Class HD+ Technology
Cooling		Heat Sink Modules & Fan
Protection		VI limiter, Direct Current Protection (DC), Short Circuit Protection, Current Limiter, Voltage Clip Limiter
Connector Input		XLR-F,XLR-M
Connector Output		NL4 SPEAKON 4 pole and Biding post per CH.
Front panel indicator		Power ON, Signal, Clip Indicator
Dimension W x D x H mm		483 x 610 x 140 mm
Power Supply		PFC Switching Mode Power Supply
Operating voltage		180 ~ 240V, 50 ~ 60Hz
Net weight		23kg

Digitclass Co.,Ltd.

7/102 Moo 2, Bangpood, Pak-Kret

Nonthaburi. 11120 Thailand.

Tel. +668 6447 4041, +66 2583-5928

Line: @digitclass

Facebook:Digitclass